

ASTM Property

Grade	FI-150
Product	Polypropylene, Homopolymer

General Information

Key Features	<ul style="list-style-type: none"> - Suitable for inflation PP film products - Excellent transparency, slipperiness and film opening property - Containing slip and anti-blocking agent
--------------	--

Applications	- Clothes packaging, food packaging
--------------	-------------------------------------

Item	Measuring Method	Unit	Value
Physical Properties			
Melt Flow Index (230°C, 2.16kg)	ASTM D1238	g/10min	11.0
Density	ASTM D792	g/cm ³	0.9
Mechanical Properties			
Tensile Stress (Yield)	ASTM D638	kgf/cm ²	350
Tensile Strain (Break)	ASTM D638	%	>500
Flexural Modulus	ASTM D790	kgf/cm ²	16,000
Rockwell Hardness	ASTM D785	R	100
Impact Properties			
Izod Impact Strength (23°C)	ASTM D256	kgf·cm/cm	3
Thermal Properties			
Melting Temperature	LDP Method	°C	162
Heat Deflection Temperature (4.6kgf/cm ²)	ASTM D648	°C	104
Film Properties			
Haze	ASTM D1003	%	<2.5

1. Physical Properties : these are not to be construed as specifications

2. Measured on 30μm mono-layer CPP film

* The last update date : 2026/06/01